

# B2PURE<sup>®</sup> - Instant Bitumen

*All B2PURE products are purely made with only two components:  
Asphaltenes and Maltene phase.*

## B2PURE<sup>®</sup> REGULAR **based on HCR 150**

<b>CO<sub>2</sub> emissions</b>	-1.200 kg CO <sub>2</sub> e/to net
<b>Temperatures</b>	processing temperatures 150 ± 5 °C
<b>Ideal Use</b>	penetration grade bitumens 70/100 and harder, including PmB 25/55-55
<b>Feature</b>	low temperature susceptibility, wide UTI

## B2PURE<sup>®</sup> STARK **based on HCR 180**

<b>CO<sub>2</sub> emissions</b>	-1.200 kg CO <sub>2</sub> e/to
<b>Temperatures</b>	processing temperatures 180 ± 5 °C
<b>Ideal Use</b>	hard grade bitumens, PmB 25/40-65, EME 2
<b>Feature</b>	27,000 kN indirect tensile strength

## B2PURE<sup>®</sup> LIGHT **based on HCR 120**

<b>CO<sub>2</sub> emissions</b>	-200 kg CO <sub>2</sub> e/to net
<b>Temperatures</b>	processing temperatures 120 ± 5 °C
<b>Ideal Use</b>	penetration grade bitumens 70/100 and softer, block bitumen applications, roofing membranes
<b>Feature</b>	very good response to polymer modifications